

WHAT'S NEW?

UL LISTING FOR EXTENDED SUPPORT DISTANCES BETWEEN HANGERS

Did you know **FRE Canada** and **FRE USA** are UL Listed for extended Support Distances per NEC article 355.30 (B)?

Our extended distances range from **2 to 3.33 times longer** than minimum distances imposed by the National Electric Code (NEC) requirements depending on conduit trade size dimension of our **HazGuard™** conduit.

The significant change generates direct labor and hardware savings since less shall be required to cover the same distance. **Savings for you to pocket!**



HazGuard™		
Trade Size (IPS)	NEC per UL Listing Table 355.30	FRE Extended Support Distances
3/4"	0,91m (3')	3m (10')
1"	0,91m (3')	3m (10')
1 1/4"	1,5m (5')	3m (10')
1 1/2"	1,5m (5')	3m (10')

Trade Size (ID)	NEC per UL Listing Table 355.30	FRE Extended Support Distances
2"	1,5m (5')	4,9m (16')
2 1/2"	1,8m (6')	4,9m (16')
3"	1,8m (6')	5,1m (17')
3 1/2"	2m (7')	5,1m (17')
4"	2m (7')	5,3m (17,5')
5"	2m (7')	5,1m (17')
6"	2,4m (8')	5,1m (17')



We are pushing further with performance way above NEC's minimum requirements. That's what we call being:

F1RST IN THE FIELD®