


# Don't Put Your Emergency Circuits at Risk!

**Atkore™**  
**FRE Composites**

 Firepumps, Emergency Feeder Cables, Ventilating Fans, Exit Lighting, Elevators, Tall Buildings, Hospitals, Oil Refineries, Drilling Platforms



**Make the safe choice -  
BreathSaver® XW Cable Fire  
Protection Conduit System**

Most complete 2-Hour Fire Rated •  
cable system (UL 2196)

UL Certified system (FHIT 25C) for 2 hours •  
both for vertical and horizontal installations

Low smoke, Emits no toxic halogen •  
(ASTM 800 C)

Lightweight 4" conduit 20 foot length •  
Fiberglass 56 lbs vs EMT 109 lbs

## 2 Hour Fire Rating - Emergency Circuits

	Competition	Lifeline RHW-2 / XW BreathSaver®
FHIT	N/A	25C
Hours	N/A	2
Conduits	N/A	3/4" - 6"
Cables	N/A	#8AWG to 750 Kcmil
Sizes	N/A	#8 AWG to 750 Kcmil
Fill	N/A	Varies - no more than 32% horizontal and 21% vertical
Vertical rise	N/A	24 Feet
Pulling lube	N/A	Polywater LZ
Pull Box	N/A	Yes - (NEMA 4X) Resolve One



[Atkore.com/fre](http://Atkore.com/fre)

US Manufacturing (719) 565-3311  
Canada Manufacturing (888) 849-9909